

PVA D3



Product Description:

Unika Water based PVA D3
Adhesive – 500g

Key Features:

- Unika PVA D3 is formulated for tongue and groove flooring – laminate or engineered woods.
- It flows easily, dries clear and is waterproof once dry.
- Unika PVA D3 is available in 500g bottles with a stepped applicator.
- Unika PVA D3 is manufactured to EN204 (D3) and DIN68602 standards and has been tested by FIRA to these standards.

Directions for Use:

When laying the floor apply Unika adhesive to the grooves, both long and short sides, according to the laying instructions.

Remove excess adhesive with a damp cloth.

Avoid treading on the floor for the next three hours.

Sufficient for 12m².

Consumer Benefits:

High performance adhesive specially formulated for the installation of laminate and engineered wood flooring.

Large bottle – 500g

Retailer Opportunity:

Unika PVA D3 is suitable for the installation of tongue and groove flooring – laminate and engineered woods.

UNIKA COLOR PRODUCTS LTD

Unika House, New York Way, New York Industrial Park,
Newcastle upon Tyne, U.K. NE27 0QF

Telephone: +44 (0) 191 259 0033

Fax: +44 (0) 191 257 4525

Email: sales@unika.co.uk www.unika.co.uk



The mark of
responsible forestry

